

SYSTEM AND METHOD FOR  
CONVERTING A PLURALITY OF WAVELENGTHS

STATEMENT OF OTHER APPLICATIONS

This application claims priority to United States  
Provisional Patent Application Number 60/212,889,  
entitled *New Wavelength Band Transmitters Using*  
5 *Modulational Instability Wavelength Converters*, filed  
June 20, 2000.

10 TECHNICAL FIELD OF THE INVENTION

The present invention relates generally to the field  
of communication systems, and more particularly to a  
system and method operable to facilitate wavelength  
conversion of a plurality of optical signals.

069204.0107

BACKGROUND OF THE INVENTION

Conventional wavelength converters typically operate to convert the wavelength of one optical signal from one wavelength to another. Problems associated with, for example, cross-talk between channels and/or polarization sensitivity have generally discouraged utilizing conventional wavelength converters in situations where it is desired to simultaneously convert numerous wavelengths using the same device.

069204.0107

SUMMARY OF THE INVENTION

The present invention recognizes a need for a method and apparatus operable to facilitate wavelength conversion of a plurality of optical signals. In accordance with the present invention, a system and method for providing wavelength conversion across a plurality of optical signals reduces or eliminates at least some of the shortcomings associated with other wavelength conversion mechanisms.

10 In one aspect of the invention, an apparatus operable to convert wavelengths of a plurality of optical signals comprises a coupler operable to receive a pump signal and a plurality of input signals each input signal comprising at least one wavelength different than the  
15 wavelengths of others of the plurality of input optical signals. The apparatus further includes an optical medium operable to receive the pump signal and the plurality of input signals from the coupler, wherein the pump signal and each of the plurality of input signals  
20 are synchronized to overlap at least partially during at least a part of the time spent traversing the optical medium to facilitate generation of a plurality of converted wavelength signals each comprising a wavelength that is different than the wavelengths of at least some  
25 of the plurality of input signals. Various embodiments can result in low cross-talk and/or low polarization sensitivity.

In another aspect of the invention, a method of generating a plurality of converted wavelength signals  
30 comprises receiving a plurality of optical input signals each comprising at least one distinct wavelength, and receiving a pump signal comprising a pump wavelength that

069204.0107

is either shorter or longer than each of the wavelengths of the plurality of input optical signals. The method further comprises copropagating the plurality of input optical signals and the pump signal over a nonlinear optical medium and generating a plurality of converted wavelength signals based on an interaction between the plurality of input optical signals and the pump signal. Various incarnations of the method can result in multiple wavelength conversion with low cross talk and/or low polarization sensitivity.

In still another aspect of the invention, a system operable to convert a plurality of wavelengths comprises one or more optical transmitters operable to generate alone or in combination a plurality of optical input signals each comprising a wavelength in a first communications band. The system also includes a multiple wavelength converter coupled to the one or more optical transmitters and operable to approximately simultaneously generate, for each of the plurality of optical input signals, a converted wavelength signal comprising a wavelength in a second communications band.

In yet another aspect of the invention, a system operable to convert a plurality of wavelengths to facilitate protection switching comprises an optical medium operable to communicate optical signals comprising wavelengths residing in a first set of wavelengths or a second set of wavelengths, and a multiple wavelength converter coupled to the optical medium. The multiple wavelength converter is operable to receive a plurality of optical signals each comprising a wavelength in the first set of wavelengths and to approximately simultaneously generate, for each of the plurality of

069204.0107

optical signals, a converted wavelength signal comprising a wavelength in the second set of wavelengths. The second set of wavelengths comprises a protection path for the first set of wavelengths. The converted wavelength  
5 signals can be generated prior to or in response to receiving notice of a fault.

Depending on the specific features implemented, particular embodiments of the present invention may exhibit some, none, or all of the following technical  
10 advantages. For example, various embodiments of the invention facilitates converting a plurality of wavelengths, even an entire band of wavelengths, while maintaining low cross-talk and/or maintaining polarization insensitivity. Some embodiments of the  
15 invention result in significant cost savings by reducing or eliminating the need for numerous costly filters to deal with harmonics created using other conversion approaches.

Some embodiments of the invention utilize a single  
20 polarization beam splitter to communicate with both inputs and outputs of a nonlinear optical medium facilitating wavelength conversion. This approach ensures that signals traversing the medium will experience identical or near identical path lengths and  
25 that the polarization of the input signals will be relatively aligned with the polarization of the pump signals.

Particular embodiments of the invention facilitate utilizing existing laser transmitters intended for use  
30 with the conventional communication band as transmitters in other communication bands. This aspect of the invention allows for initially generating input optical

069204.0107

signals using, for example, C-band transmitters, and then utilizing a multiple wavelength converter to approximately simultaneously convert all of the input signals to wavelengths of another band, such as the  
5 S-band or L-band. This approach can save significant resources associated with developing new laser transmitters and can facilitate quick and inexpensive system upgrades.

Other technical advantages are readily apparent to  
10 one of skill in the art from the attached figures, description, and claims.

069204.0107

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention, and for further features and advantages thereof, reference is now made to the following  
5 description taken in conjunction with the accompanying drawings, in which:

FIGURES 1a-1b are block diagrams of an exemplary multiple wavelength converters implemented in communication systems according to the teachings of the  
10 present invention;

FIGURES 2a-2b are spectral diagrams illustrating various operational aspects of particular embodiments of a multiple wavelength converter;

FIGURES 3a-3d are spectral diagrams illustrating  
15 various stages of wavelength conversion;

FIGURES 4a-4d are block diagrams showing various embodiments of a low cross-talk multiple wavelength converter;

FIGURE 5 is a graph illustrating cross-talk  
20 performance of one embodiment of a multiple wavelength converter constructed according to the teachings of the present invention;

FIGURE 6 is a graph illustrating polarization sensitivity associated with one embodiment of a multiple  
25 wavelength converter;

FIGURES 7a-7c are block diagrams showing various embodiments of polarization insensitive multiple wavelength converters;

FIGURE 8 is a graph illustrating improvements in  
30 polarization sensitivity realized by one embodiment of a polarization insensitive multiple wavelength converter;

09885678-062001  
100290-8298860

FIGURE 9 is a flow chart illustrating one example of a method of converting a plurality of wavelengths while maintaining low cross-talk; and

FIGURE 10 is a flow chart illustrating one example  
5 of a method of converting a plurality of wavelengths while maintaining low polarization sensitivity.

09885678-062001



DETAILED DESCRIPTION OF THE INVENTION

Conventional optical communication systems have traditionally implemented optical signals having wavelengths in the conventional communications band (C-band). As the use of data intensive applications becomes increasingly prevalent, the need for additional bandwidth continues to escalate. One mechanism for supplying additional bandwidth in optical communication system is to utilize optical signals having wavelengths outside of the conventional communication band. For example, optical signals having wavelengths in the long communications band (L-band) or the short communications band (S-band) could be utilized to provide additional bandwidth.

One aspect of this invention recognizes that, for a number of reasons, it would be desirable to design a wavelength converter operable to convert a plurality of wavelengths, even a whole band of wavelengths, simultaneously using the same device. As used in this document, the concept of "simultaneously" converting wavelengths refers to at least beginning generation of one converted wavelength before another converted wavelength is fully generated. Interaction of pump signals with input optical signals to form converted wavelength signals is a sequential process continuing to occur as the signals traverse an optical medium. Simultaneous conversion does not require that all converted wavelengths be formed at precisely the same time.

FIGURE 1a is a block diagram of an exemplary multiple wavelength converter 12 implemented in an optical communication system 10. In this example, system

09885673-062001

10 includes a plurality of laser diodes 14a-14n. Each laser diode 14 is operable to generate an optical signal having at least one wavelength that is distinct from wavelengths generated by other laser diodes 14.  
5 Alternatively, a single laser transmitter operable to generate a plurality of wavelength signals could be implemented.

System 10 also includes an optical coupler 16. As a particular example, coupler 16 may comprise a wavelength  
10 division multiplexer (WDM) operable to receive a plurality of signals having different wavelengths and to combine those signals into a wavelength division multiplexed signal, a dense wavelength multiplex signal, or other signal carrying multiple wavelengths.

15 System 10 includes a multiple wavelength converter 12 operable to receive the plurality of input optical signals 18 having wavelength  $\lambda_1$ - $\lambda_n$  and to generate a plurality of converted wavelength signals  $\lambda_1'$  -  $\lambda_n'$ . In particular embodiments, multiple wavelength converter 12  
20 can comprise a polarization insensitive and/or low cross-talk wavelength converter.

One application for multiple wavelength converter is as a multiple wavelength converter facilitating use of transmitters designed to operate at one wavelength to  
25 produce optical signals at other wavelengths. For example, a multiple wavelength converter could be used to facilitate generation of optical signals in the S-band and/or the L-band using laser transmitters designed to produce signals in the C-band of wavelengths. Optical  
30 signals having wavelengths in the C-band could first be produced using conventional laser transmitters, and then be converted to another band using a multiple wavelength

09885678-052001

converter. This approach allows service providers to offer services in alternative communications bands without incurring significant expenses associated with designing and/or implementing new lasers operable to  
5 generate signals in the alternative bands.

FIGURE 1B is a block diagram showing a similar multiple wavelength converter 12 implemented in a protection switching scheme. In the event of a full or a partial fiber cut, or other event affecting fiber  
10 carrying one band of wavelengths but not another band of wavelengths, or affecting one fiber and not another fiber, a band converter would be useful in switching the optical traffic utilizing the disabled band to another band or bands of wavelengths.

Wavelength converter 12 in FIGURE 1B couples to optical medium 15 comprising a first communication path 17a and a second communication path 17b. In this example, first communication path 17a comprises a first fiber and second communication path 17b comprises a  
15 second fiber. Alternatively, paths 17a and 17b could reside as separate portions of a common fiber.

In this example, first communication path 17a carries optical traffic on wavelengths  $\lambda_1$ - $\lambda_n$ . Second communication path 17b comprises a protection path  
20 operable to carry wavelengths  $\lambda_1$ - $\lambda_n$ . Multiple wavelength converter 12 can convert wavelengths  $\lambda_1$ - $\lambda_n$  to wavelengths  $\lambda_1$ - $\lambda_n$  for communication over first communication path 17a and/or second communication path 17b. In one example, wavelength converter 12 may convert and propagate a  
25 protection version of the traffic to the converted wavelengths ready for switching in the event of a fault. In another example, wavelength converter 12 could convert  
30

069204.0107

the normal traffic to protection traffic upon detecting a fault. The fault could be associated, for example, with the communication path or the optical signals themselves.

As a particular example, communication paths 17a and  
5 17b could facilitate communication of separate communication bands. For example, first communication path 17a could carry signals having wavelengths in the C-band, while protection path 17b could carry signals comprising wavelengths from the S-band or the L-band.

10 These examples illustrate just some of the variety of applications for which a multiple wavelength converter would be advantageous.

FIGURES 2a-2b are spectral diagrams illustrating various operational aspects of particular embodiments of  
15 a multiple wavelength converter 12. In operation, multiple wavelength converter 12 receives a plurality of input optical signals 18 having wavelengths  $\lambda_1$ - $\lambda_n$ . In this particular example, input optical signals 18 comprise signals from the C-band. Input optical signals  
20 18 could alternatively reside in another communications band.

In operation, multiple wavelength converter 12 introduces a pump signal 30 having wavelength  $\lambda_p$  so that pump signal 30 copropagates with input optical signals 18  
25 along a nonlinear optical medium of wavelength converter 12. Wavelength  $\lambda_p$  of pump signal 30 is selected to be either shorter or longer than each of the wavelengths of optical input signals 18. In this manner, as pump signal 30 interacts with optical input signals 18 as those  
30 signals traverse the nonlinear optical medium, a mirror image of optical input signals 18 is generated at wavelengths residing spectrally opposite from optical

069204.0107

input signals 18 and pump signal 30. As used in this document, the term "mirror image" is intended to denote a situation where wavelengths of the input signals residing on one side of the pump wavelength are reflected to the other side of the pump signal by approximately a distance equal to that signal's distance from the pump signal. Crowning effects that can sometimes result in the amplitudes of the converted wavelength signals not precisely matching the amplitudes of each of the input signals are not intended to exclude a spectrum from being considered a "mirror image."

Converted wavelength signals 20 generated through interaction between pump signal 30 and input optical signals 18 result from a Chi-3 nonlinear effect or an effective Chi-3 nonlinear effect. Examples of these Chi-3 effects are four wave mixing (4WM), parametric amplification, and modulation instability. Modulation instability and parametric amplification occur where the wavelength of pump signal 30 is greater than the zero-dispersion wavelength ( $\lambda_0$ ) of the nonlinear medium. Four Wave Mixing occurs where the wavelength of pump signal 30 is selected to be less than the zero-dispersion wavelength of the medium. An effective Chi-3 nonlinear effect can be achieved, for example, by cascading two or more media exhibiting a Chi-2 nonlinear effect. These are just a few examples of nonlinear phenomena that can be used to generate converted wavelength signals 20 by allowing a pump signal 30 to interact with optical input signals 18.

Although the examples shown in FIGURES 2a-2b depict converting a plurality of optical signals 18 from the C-band to another band, converter 12 could also operate

069204.0107

to convert optical signals initially residing in the S-band or the L-band to another communication band. Moreover, multiple wavelength converter 12 could be used to convert multiple wavelengths within the same band. It is not necessary that the optical input signals and the converted wavelength signals reside in separate communication bands.

FIGURES 3A-3D are spectral diagrams illustrating various stages during the generation of converted wavelength signals 20. FIGURE 3A shows a spectrum of input optical signals 18 and pump signal 30. In this example, it is desired to generate a plurality of converted wavelength signals 20 at wavelengths shorter than any of input optical signals 18. To facilitate this operation, the wavelength  $\lambda_p$  of pump signal 30 is selected to reside between the wavelengths of input optical signals 18 and the wavelengths of converted optical signals 20 to be generated.

In operation, multiple wavelength converter 12 propagates pump signal 30 and input optical signals 18 so that pump signal 30 and input optical signals 18 overlap for at least a portion of their transmission time over the nonlinear optical medium. While these signals overlap, pump signal 30 interacts with input optical signals 18 to begin to generate an initial plurality of converted wavelength signals 20' as shown in FIGURE 3B. The longer the span of the nonlinear medium over which pump signal 30 and optical input signals 18 overlap, the greater the interaction between those signals. FIGURE 3B shows that over a short length of nonlinear optical medium allowing for little interaction between pump signal 30 and input signals 18, the amplitude of initial

069204.0107

converted wavelength signals 20' is small compared to the amplitude of the original input signals 18.

FIGURE 3C illustrates converted wavelength signals 20 after further interaction between pump signal 30 and input signals 18 over a longer span of nonlinear optical medium. At some point, depending on, for example, the characteristics of the nonlinear optical medium, the characteristics of pump signal 30, and/or the characteristics of input signals 18, a length of the nonlinear optical medium can be implemented that facilitates generation of converted wavelength signals 20 whose amplitudes approach the amplitudes of input signals 18. FIGURE 3C shows one example of this scenario.

Applicants realize, however, that if the length of the nonlinear optical medium becomes too great, the interaction between pump signal 30 and other optical signals propagating along the optical medium creates harmonics as shown in FIGURE 3D. These harmonics become interspersed throughout converted wavelength signals 20, resulting in cross-talk between the converted wavelength signals and the harmonics.

Single wavelength converters exist, which rely on a Chi-3 nonlinear effect to produce one converted wavelength signal. Traditionally, these converters have dealt with harmonics by implementing filters to separate the converted wavelength signal from the harmonic. In a multiple wavelength converter, relying solely on this approach to deal with the cross-talk caused by harmonics can be extremely expensive, or even impossible depending on the number of wavelengths being converted.

One aspect of some embodiments of this invention seeks to reduce cross-talk generated in converting

069204.0107

multiple wavelengths of signals by selecting a propagation length of nonlinear optical medium that will provide adequate conversion efficiency but reduce the effects of cross-talk caused by harmonics in the converted wavelength spectrum. In particular, rather than relying solely on removal of harmonics from the converted wavelength spectrum, as single wavelength converter approaches have done, this approach seeks to optimize the length of the nonlinear optical medium to reduce generation of harmonics in the first place.

FIGURES 4A-4D are block diagrams illustrating various embodiments of low cross-talk multiple wavelength converters. FIGURE 4A is a block diagram of one particular embodiment of a low cross-talk multiple wavelength converter 112. In this example, multiple wavelength converter 112 includes a coupler 140 operable to receive pump signal 30 having a wavelength  $\lambda_p$  and input optical signals 18 having wavelengths ranging from  $\lambda_1$ - $\lambda_n$ . Wavelength division multiplexers, optical taps, and polarization beam splitters are a few examples of devices that could be implemented as coupler 140.

Coupler 140 communicates with a nonlinear optical medium 150. Nonlinear optical medium 150 could comprise, any medium operable to facilitate interaction between pump signal 30 and optical input signals 18 to result in a Chi-3 or an effective Chi-3 nonlinear effect. A length of high nonlinearity fiber or a nonlinear crystal are examples of materials that could be implemented. Nonlinear optical medium 150 comprises a propagation length (L). Propagation length (L) represents a length over which pump signal 30 and optical signals 18 can interact to result in a Chi-3 or effective Chi-3

09885678-062001



nonlinear effect and a corresponding reflection of optical signals 18 about pump wavelength  $\lambda_p$ . The propagation length (L) of nonlinear medium 150 is selected to provide adequate conversion efficiency to converted wavelengths 20, while minimizing cross-talk by preventing or reducing generation of harmonics in the spectrum of converted wavelength signals 20. Although the illustrated embodiment shows nonlinear optical medium 150 coupled directly to coupler 140, any optical medium could reside between coupler 40 and nonlinear optical medium 150.

In this particular example, multiple wavelength converter 112 includes a filter 160 operable to block particular wavelengths from propagating to output 170. As a particular example, filter 160 could be designed to block the wavelength of pump signal 30 and/or input optical signals 18, and to allow converted wavelength signals 20 to pass.

FIGURE 4B is a block diagram of another embodiment of a low cross-talk multiple wavelength converter 212. Multiple wavelength converter 212 is similar in structure and function to converter 112 shown in FIGURE 4A. Converter 212, however, implements a polarization filter 255 to block the pump wavelength  $\lambda_p$ .

FIGURE 4C is a block diagram showing still another embodiment of a low cross-talk multiple wavelength converter 312. Nonlinear optical medium 350 of multiple wavelength converter 312 comprises a nonlinear optical looped mirror operable to receive input optical signals 18 and pump signal 30 from a coupler 352. In this embodiment, coupler 352 comprises a 2x2 dichroic coupler,

09885678-062001

In operation, coupler 352 propagates input optical signals 18 in a clockwise direction around loop 352, propagates approximately half of the pump power in a clockwise direction, and approximately half in a counter-clockwise direction. A pump wavelength filter 360 can be used to reflect pump light back to the coupler 352 if desired.

Regardless of the particular embodiment of the multiple wavelength converter 112, 212, 312, or 412, the propagation length of nonlinear optical media 150, 250, 350, and 450, respectively, are chosen to provide  
25 adequate conversion efficiency while reducing cross-talk by suppressing the onset of harmonics in the converted wavelength spectrum.

For example, some embodiments of multiple wavelength converters may generate converted wavelength signals 20 at a conversion efficiency of at least minus sixteen (-16) decibels while introducing a cross-talk of less than minus fourteen (-14) decibels over a wavelength range of

at least seven (7) nanometers. Other embodiments may generate converted wavelength signals 20 at a conversion efficiency of at least 4.7 decibels while introducing a cross-talk of less than minus twenty-seven (-27) decibels  
5 over a wavelength range of at least thirty (30) nanometers.

Many communication systems require bit error rates of no more than  $10^{-9}$ , or even  $10^{-10}$ . A bit error rate of  $10^{-9}$  corresponds to a cross talk of approximately -17  
10 decibels with a 0.5 decibel power penalty. A bit error rate of  $10^{-10}$  corresponds to a cross talk of approximately -25 decibels with a 0.5 decibel power penalty. One aspect of the invention facilitates meeting these requirement through, for example, appropriate selection  
15 of a propagation length of the converter. In this manner, multiple wavelengths can be converted while maintaining acceptable bit error rates.

These performance parameters are presented for exemplary purposes only. Wavelength converters having  
20 other performance characteristics are not intended to be excluded from the scope of the invention.

FIGURE 5 is a graph showing experimental results of measured cross-talk for a particular embodiment of a low cross-talk multiple wavelength converter. In this  
25 example, the pump wavelength  $\lambda_p$  was selected to be 1,532 nanometers and the pump power set to 860 milliwatts. The signal power per channel comprises 7 microwatts. The nonlinear optical medium was selected to be a high nonlinearity fiber having a zero-dispersion wavelength of  
30 approximately 1,530 nanometers, a loss of approximately one decibel per kilometer, a nonlinearity constant ( $\gamma$ ) of approximately  $9.9 \text{ watts}^{-1}\text{kilometer}^{-1}$ , and a dispersion

069204.0107

slope  $(\Delta D/\Delta \lambda)$  of approximately 0.0265 picoseconds/nanometer<sup>2</sup>\*kilometer. In this example, the propagation length 150 comprises 315 meters. Using this configuration, a conversion efficiency of at least 4.7  
5 decibels is obtained, while cross-talk consistently remains at -27 decibels or less over the converted bandwidth.

The results depicted and configuration associated with in FIGURE 5 are for exemplary purposes only. Other  
10 fiber types and signal characteristics could be implemented without departing from the scope of the invention.

FIGURE 6 is a graph illustrating polarization sensitivity measured for the low cross-talk multiple  
15 wavelength converter discussed with respect to FIGURE 5. Without implementing a polarization control mechanism, the polarization of pump signal 30 and the polarization of each input optical signal 18 can vary over time. Depending on the relative polarizations of each of those  
20 signals, the gain experienced by the wavelength converter can vary. The term polarization sensitivity refers to the difference between the maximum gain and the minimum gain of the device over time. As shown in FIGURE 6, while a device such as those shown in FIGURES 4A-4D can  
25 result in a reduction of cross-talk, without further modification, those devices can be subject to significant polarization sensitivity. With respect to the particular example discussed in FIGURE 5, that device exhibits polarization sensitivities averaging approximately 2.5  
30 decibels. One aspect of the invention seeks to minimize polarization sensitivity in multiple wavelength converters.

09885678-062001

FIGURE 7A-7C are block diagrams of various embodiments of polarization insensitive multiple wavelength converters. Multiple wavelength converter 512 shown in FIGURE 7A includes a coupler 540 operable to receive pump signal 30 and optical input signals 18. Coupler 540 may comprise, for example, a wavelength division multiplexer, an optical tap, or a polarization beam splitter. Coupler 540 communicates with a polarization beam splitter 542. In this example, polarization beam splitter 542 comprises a plurality of ports. An input port 543 receives pump signal 30 and input optical signals 18. Ports 544 and 545 communicate with a nonlinear optical medium 550. In this example, nonlinear optical medium 550 couples directly to ports 544 and 545. Alternatively, additional optical links, such as optical fibers, could couple nonlinear optical medium 550 to ports 544 and 545. In this example, nonlinear optical medium 550 comprises a high nonlinearity fiber. Alternatively, nonlinear optical medium 550 could comprise a nonlinear crystal, or other medium operable to facilitate a Chi-3 or an effective Chi-3 effect due to interaction between pump signal 30 and input optical signals 18.

Polarization beam splitter 542 also includes an output port 546. Optical signals can be directed from polarization beam splitter 542 through output port 546, through input port 543, or through a combination of those ports. Where converted wavelength signals 20 exit polarization beam splitter 542 through input port 543, a circulator or other device could be used to redirect converted wavelength signals 20 from the path of input signals 18.

069204.0107

A polarization controller 555 could be used to control direction of signals traversing optical medium 550 by maintaining or adjusting polarizations of those signals. Alternatively, optical medium 550 could  
5 comprise a polarization maintaining fiber to ensure that all or most of the converted wavelength signals 20 leave polarization beam splitter 542 through a common port.

In operation, polarization beam splitter 542 receives pump signal 30 and optical input signals 18 at  
10 input port 543. Polarization beam splitter 542 separates portions of the received signals having a first polarization from portions having a second polarization orthogonal to the first polarization. In this example, first portion 30a of pump signal 30 and first portions  
15 18a of input optical signals 18 comprise a vertical (s) polarization, while second portion 30b of pump signal 30 and second portions 18b of optical input signals 18 comprise a horizontal (p) polarization.

Polarization beam splitter 542 communicates signal  
20 portions having the first polarization clockwise around loop 550 and communicates signal portions having the second polarization counter-clockwise around loop 550. Of course, leakage portions of the first polarization may travel in a counter-clockwise direction and leakage  
25 portions of the second polarization may travel in a clockwise direction. These circumstances are not intended to be outside of the scope of the invention.

Nonlinear optical medium 550 facilitates at least substantially unidirectional interaction between first  
30 portion 30a of pump signal 30 and first portions 18a of optical input signals 18 to generate first portions of converted wavelength signals 20 each having at least

069204.0107

substantially the first polarization. Similarly,  
nonlinear optical medium 550 facilitates at least  
substantially unidirectional interaction between second  
portion 30b of pump signal 30 and second portions 18b of  
5 optical input signals 18 to generate second portions of  
converted wavelength signals 20 having at least  
substantially the second polarization.

Optical scattering that can typically occur as  
signals traverse an optical medium is not intended to be  
10 outside of the scope of the phrase "unidirectional  
interaction" as used herein.

Polarization beam splitter 542 combines the first  
and second portions of converted wavelength signals 20.  
In this example, polarization beam splitter 542  
15 communicates converted wavelength signals 20 from output  
port 546. These signals could alternatively be  
communicated from another port, such as input port 543.

For low polarization sensitivity, it is desirable to  
ensure that first portion 30a of pump signal 30 and  
20 second portion 30b of pump signal 30 have at least  
approximately equal powers. Numerous mechanisms can  
accomplish this goal. For example, if it is desired to  
use a single pump signal, pump signal 30 can be launched  
at an angle of 45 degrees to ensure that approximately  
25 half of the power of pump signal 30 travels in each  
direction around loop 550. This can be implemented, for  
example, by implementing a polarization controller 525  
operable to adjust the angle of pump signal 30 to  
approximately 45 degrees. In a particular embodiment,  
30 optical link 535 between coupler 540 and polarization  
beam splitter 542 could comprise a polarization  
maintaining fiber to ensure that the angle of pump signal

069204.0107

30 remains approximately 45 degrees when it reaches polarization beam splitter 542.

FIGURES 7B and 7C show alternative embodiments using separate pump signals to achieve similar results. For example, multiple wavelength converter 612 shown in FIGURE 7B implements a first pump signal 30a having an approximately vertical polarization and a second pump signal 30b having an approximately horizontal polarization. First and second pump signals 30a and 30b are combined by a polarization beam splitter 623 to form pump signal 30 at an angle of approximately 45 degrees. Pump signal 30 and optical input signals 18 copropagate from coupler 640 to polarization beam splitter 642. Again, a polarization maintaining fiber 635 can be used to approximately maintain the polarization of pump signal 30 between coupler 640 and polarization beam splitter 642. At this point, multiple wavelength converter 612 operates in a similar manner to converter 512 described with respect to FIGURE 7A.

Multiple wavelength converter 712 shown in FIGURE 7C also implements two separate pump signals 30a and 30b, but combines those signals with optical input signals 18 within loop 750. In this embodiment, polarization beam splitter 742 receives input optical signals 18 at input port 743. Polarization beam splitter 742 directs signal portions having a first polarization in one direction around loop 750 and signal portions having a second polarization in an opposite direction around loop 750. In this particular example, signal portions 18a having a vertical polarization are directed in a clockwise direction around loop 750, while signal portions 18b

069204.0107



having a horizontal polarization are directed in a counter-clockwise direction around loop 750.

In this example, multiple wavelength converter 712 includes couplers 756 and 758 residing between loop 750 and ports 744 and 745 of polarization beam splitter 742. First coupler 756 receives first pump signal 30a having a vertical polarization and combines pump signal 30a with portions 18a of optical input signals 18 also having a vertical polarization. Nonlinear optical medium 750 facilitates at least substantially unidirectional interaction between first pump signal 30a and first signal portions 18a to facilitate generation of first portions of converted wavelength signals 20 comprising instances of input signals 18 reflected about pump wavelength  $\lambda_p$ .

In a similar manner, coupler 758 combines second pump signal 30b having a horizontal polarization with second portions 18b of optical input signals 18 also having horizontal polarization. Nonlinear optical medium 750 facilitates at least substantially unidirectional interaction between the horizontally polarized signal portions to result in generation of second portions of converted wavelength signals 20. Polarization beam splitter 742 combines the first and second portions of the converted wavelength signals to form converted wavelength signals 20.

Implementing a single polarization beam splitter coupled to both inputs of a nonlinear optical medium provides significant advantages over approaches attempting to use multiple polarization beam splitters to join multiple physically separate optical paths. For example, Applicants recognize that using a single

09885678.062001

polarization beam splitter coupled to both ends of a nonlinear optical medium ensures that the multiple optical paths traveling along the same physical medium will always have identical lengths. In addition, this approach reduces the possibility that one optical path will be adversely affected by environmental forces, such as temperature or pressure variations, while the other is not.

FIGURE 8 is a graph illustrating polarization sensitivities in various multiple wavelength converter configurations. Line 810 shows polarization sensitivity for a multiple wavelength converter configuration such as that shown in FIGURE 4A for a propagation length of approximately 280 meters. Line 820 shows polarization sensitivity for the same configuration of a multiple wavelength converter using a propagation length of approximately 400 meters. Line 830 shows the reduction in polarization sensitivity obtained using a configuration such as that shown in FIGURE 7A for a propagation length of approximately 400 meters. Line 840 shows polarization sensitivity for a similar configuration using a propagation length of approximately 280 meters.

As demonstrated here, implementing a multiple wavelength converter utilizing a single polarization beam splitter to communicate with both ends of a single nonlinear optical medium can result in a significant reduction in polarization sensitivity. Particular embodiments of these types of configurations exhibit polarization sensitivities of less than 2.0 decibels over wavelength ranges of at least seven (7) nanometers. In fact, some configurations have been shown to achieve

069204.0107

polarization sensitivities of less than 0.6 decibels over wavelength ranges larger than thirty-five (35) nanometers.

Of course, aspects of the invention relating to  
5 reduction of polarization sensitivity can be combined  
with aspects of the invention relating to reduction of  
cross-talk. For example, by implementing a configuration  
such as those shown in FIGURE 7A-7C and by selection of  
the propagation length of the nonlinear optical medium in  
10 light of the characteristics of that medium and of the  
signals being processed, polarization insensitive  
multiple wavelength converters can be created with low  
levels of cross-talk.

FIGURE 9 is a flow chart illustrating one example of  
15 a method 900 of converting the wavelengths of a plurality  
of optical signals while maintaining low levels of  
cross-talk. This example will be described using  
multiple wavelength converter 112 discussed with respect  
to FIGURE 4a. Discussions relating to that particular  
20 configuration are intended for illustrative purposes  
only. Other embodiments of a multiple wavelength  
converter could be used without departing from the scope  
of the invention.

Method 900 begins at step 910 where multiple  
25 wavelength converter 112 receives a plurality of optical  
input signals 18. Optical input signals 18 each comprise  
at least one wavelength distinct from the wavelengths of  
others of input signals 18. In a particular embodiment,  
each of input signals 18 may comprise a wavelength  
30 residing in a first subset of wavelengths, such as a  
communications band.

09835678-062004  
T.00290-8/998860

Multiple wavelength converter 112 receives pump signal 30 at step 920. Pump signal 30 comprises an optical signal having a wavelength that is either shorter than or longer than each of the wavelengths of optical signals 18. In this particular example, multiple wavelength converter 112 receives input signals 18 and pump signal 30 at an optical coupler 140.

Optical coupler 140 communicates pump signal 30 and input signals 18 to optical medium 150. Pump signal 30 and input signals 18 copropagate over optical medium 150 at step 930. During at least a portion of the time those signals traverse optical medium 150, those signals overlap and interact to generate a plurality of converted wavelength signals at step 940. In particular, input signals 18 and pump signal 30 interact to cause a Chi-3 or effective Chi-3 nonlinear effect, which operates to generate an approximate mirror image of input signals 18 reflected about the wavelength of pump signal 30. At least some of the converted wavelength signals resulting from this interaction reside within a subset of wavelengths distinct from the subset containing input signals 18. In a particular example, converted wavelength signals 20 reside in a separate communications band from input signals 18.

By appropriate selection of, for example, a propagation length of optical medium 150, multiple wavelength converter 112 achieves a desired conversion efficiency, while maintaining low cross-talk by reducing the creation of harmonics.

FIGURE 10 is a flow chart showing one example of a method 1000 of converting the wavelengths of a plurality of signals while maintaining an acceptable polarization

069204.0107

sensitivity. This example will be described with respect to multiple wavelength converter 512 as shown in FIGURE 7a. Other embodiments of multiple wavelength converters could implement this or similar methods without departing  
5 from the scope of the invention.

Method 1000 begins at step 1010 where multiple wavelength converter 512 receives at polarization beam splitter 542 a plurality of optical input signals 18. Polarization beam splitter 542 separates each of the  
10 plurality of optical input signals 18 into a first portion and a second portion at step 1020. In this example, the first portion of 18a of each optical input signal 18 comprises a first polarization, for example a vertical polarization, while second portion 18b comprises  
15 a second polarization, for example a horizontal polarization.

Multiple wavelength converter 512 copropagates first portions 18a and first pump signal 30a in a first direction along nonlinear optical medium 550 at step  
20 1030. Similarly, multiple wavelength converter 512 copropagates second portions 18b of input signals 18 along and second pump signal 30b in a second direction opposite from the first direction around nonlinear optical medium 550 at step 1040. In this example, first  
25 pump signal 30a and second pump signal 30b comprise two portions of a common pump signal 30 separated according to their respective polarizations. Pump signal 30, for example could be launched at an angle of 45 degrees so that polarization beam splitter 542 communicates  
30 approximately one half of pump signal 30 in each direction around optical medium 550. In another embodiment, first pump signal 30a and second pump signal

069204.0107

30b could comprise pump signals generated from separate pump sources. Multiple wavelength converters 612 and 712 of FIGURE 7b and 7c, respectively, illustrate examples of this type of embodiment.

5 As first portions 18a of input signal 18 and first pump signal 30a propagate along optical medium 550, they interact generating a Chi-3 or effective Chi-3 nonlinear effect. The Chi-3 nonlinear effect may comprise, for example, parametric amplification, modulation  
10 instability, or four wave mixing. The interaction between input signal 18a and pump signal 30a generates first portions of converted wavelength signals 30, which are received at port 545. Likewise, interaction between second portions 18b and second pump signal 30b along  
15 optical medium 550 generate second portions of converted wavelength signals 20, which are received at port 544.

Multiple wavelength converter 512 combines the first and second portions of converted wavelength signals 20 at step 1050 to form the plurality of converted wavelength  
20 signals 20. Converted wavelength signals 20 comprise an approximate mirror image of input optical signals 18 reflected about the wavelength of pump signal 30. Converted wavelength signals 20 can be output from multiple wavelength converter 512 through one or more  
25 ports. In the illustrated embodiment, all converted wavelength signals 20 are output from port 546. To insure that all converted wavelength signals can be removed from a single port, a polarization controller 555 can be used to maintain polarization of the signals as  
30 they traverse optical medium 550. Alternatively, optical medium 550 could comprise a polarization maintaining fiber.

09885678-062001

In another embodiment, converted wavelength signals  
20 could be output from input port 543. In that case, a  
circulator, or other device operable to redirect optical  
signals could be used to direct converted wavelength  
5 signals 20 from the path of signals incoming to port 543.

Using a single polarization beam splitter coupled to  
a common optical medium can provide significant  
advantages in controlling the polarization sensitivity of  
the converter. Particular embodiments may exhibit  
10 polarization sensitivities less than 2 decibels, or even  
less than 0.6 decibels over a wavelength range of more  
than thirty-five (35) nanometers, depending on particular  
configurations implemented. In addition, the propagation  
length of the optical medium in this case could also be  
15 selected to result in low cross-talk over the band of  
converted wavelengths signals 20.

Although the present invention has been described in  
several embodiments, a myriad of changes, variations,  
alterations, transformations, and modifications may be  
20 suggested to one skilled in the art, and it is intended  
that the present invention encompass such changes,  
variations, alterations, transformations, and  
modifications as fall within the spirit and scope of the  
appended claims.

09835678-062004